

60M HDMI Extender
(Support 3D -1080P, IR control)

The Extender uses single a Cat-5E or Cat-6(recommended) cable instead of HDMI cable to transmit high definition signal up to 60 meters. The Extender is designed to supply for long distance transmission with 1080p/60Hz signal.

Our devices offer solutions for notes, space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.


FEATURES

- Support HDMI 1.4a
- Support 3D
- Support IR extension
- Support highest video resolution 1080p/60Hz
- Support 1.5Gbps data rate and Imds clock up to 148.5MHz
- Support 8 bit deep color
- Support AWG28 HDMI standard cable, input up to 10 meters, output up to 10 meters
- Signal transmission: By using single cat-5e or cat-6(recommended) cable instead of HDMI cable, it can extend the distance up to 60 meters between TX and RX.
- No loss of quality
- Install in minutes
- Need 1pc B/GVA POC power supply (can support one way power supply, but only support TX one way supply)

Product Picture:



Physical Connection Showing Picture:



Operating and Connecting:

- Connect one HDMI cable between source device and TX Extender, the max cable distance is 10 meters
- Connect one HDMI cable between display device and RX Extender, the max cable distance is 10 meters
- Connect TX and RX Extender via single cat 5E/6 cable, the max distance is 60 meters
- Pls insert the IR RX cables and IR TX cables into the ports of IR RX and IR TX on Transmitter and Receiver
- Connect 5V power supply to the TX and RX.
- LED Indicator light
TX LED indicator light: When there is no signal input, it turns blue; When there is signal input, it turns red.
RX LED indicator light: When there is no signal input, it turns blue; When there is signal input, it turns red.

SPECIFICATIONS:

Length of CAT-6(Cat-5E) cable between RX and TX.....Up to 60 meters
HDMI Input.....24/50/60Hz/1080p/1080i/720p/576p/576i/480p/480i
Support audio.....DTS/Dolby/DSD
HDMI Output.....24/50/60Hz/1080p/1080i/720p/576p/576i/480p/480i
Max bandwidth.....148.5MHz
Max baud rate.....1.5 Gbps
Input video signal.....0.5~1.5Vdds p-p
Output DDC signal.....5Vdds p-p (TTL)
Input HDMI cable distance.....≤15m AWG28 HDMI standard cable
Output HDMI cable distance.....≤15m AWG28 HDMI standard cable
TX Max working current.....≤10mA
RX Max working current.....≤10mA
Power adapter format.....Input:AC (50Hz, 60Hz) 100V-240V; Output:DC5V/2A
Operating Temperature range.....(-15 to +55 °C)
Operating Humidity range.....5 to 90%RH (No Condensation)
Dimension (L x W x H).....83*55.3*22.8 (mm)
TX Weight.....100g
RX Weight.....120g

The Package includes:

- TX Extender x 1 pcs
- RX Extender x 1 pcs
- DC-5V Power adapter x 1 pcs
- 1pc IR TX cable, 1pc IR RX cable
- User Manual

Note pls :

- Pls use the machine as the instruction listed to keep the long use lifetime of the machine.
- The machine should be placed at the spot far from the Damp, High-Temperature, Dusty, Explosive and corrosive environment.
 - All parts will be free from the strong shake, hit, fall.
 - Touching the power adaptor with the wet hands is prohibited.
 - Pls hold the power adaptor head and do not pull the power cord when cut off from the socket.
 - Pls turn the power off when the machine is not used for long time.
 - Pls do not open the cover and do not touch the inside parts.
 - Pls use the original factory power adaptor.

Before power on, pls check the connection line carefully. And make sure that all interfaces are normally connected. The common trouble shooting way shows below:

Serial NO	Trouble Description	Cause and Ways to deal with
1	Non-Power-Connected	1. Check if the power plug is truly and correctly inserted the power socket. 2. Check the power switch if it is in on status.
2	No Picture	1. Pls to make sure that the TV is on and has been connected with the machine. 2. To check if the signal source is on and well connected. 3. Check the system connection quality. 4. Check if the line is all good quality. 5. Check the cable quality
3	Obscure Picture	1. To try again to connect the cable to be free from the unsuccessful connection. 2. HDMI Cable Quality/ HDMI Standard cable)